

CONTENTS

	<i>Page</i>		<i>Page</i>
List of figures	iv	10.6 DESIGN CHECK NO. 6—	
List of tables	iv	Design capacity of supported	
Preface	v	member (Shear—uncoped or	
About the author	vi	coped)	18
About the contributing author and editor	vi	10.7 DESIGN CHECK NO. 7—	
Acknowledgements	vii	Design capacity of supported	
		member (Bending of coped	
1 CONCEPT OF DESIGN GUIDES.....	1	section)	19
1.1 Background	1	10.8 DESIGN CHECK NO. 8—	
2 DESCRIPTION OF CONNECTION	2	Beam rotation check	20
3 TYPICAL DETAILING OF CONNECTION ..	3	10.9 DESIGN CHECK NO. 9—	
4 DETAILING CONSIDERATIONS.....	4	Local stability of coped	
5 COMPLIANCE WITH AS 4100		supported member	21
REQUIREMENTS FOR CONNECTIONS ...	6	10.10 DESIGN CHECK NO. 10—	
6 BACKGROUND INFORMATION	7	Local capacity of supporting	
7 BASIS OF DESIGN MODEL.....	9	member	22
8 FULL DEPTH END PLATES	10	10.10.1 Single-sided connection	22
9 CONNECTION GEOMETRY	11	10.10.2 Double-sided connection	23
10 RECOMMENDED DESIGN MODEL—		11 OTHER DESIGN CONSIDERATIONS	24
SUMMARY OF CHECKS	12	12 REFERENCES.....	25
10.1 DESIGN CHECK NO. 1—		13 DESIGN EXAMPLE.....	26
Detailing limitations	13	13.1 Design example No. 1—	
10.2 DESIGN CHECK NO. 2—		Connection capacity with single-	
Design capacity of weld to		sided coped FEP connection to	
supported member	14	supporting UB	26
10.3 DESIGN CHECK NO. 3—		14 DESIGN CAPACITY TABLES	29
Design capacity of bolt group	15	14.1 Configuration A—Member	
10.4 DESIGN CHECK NO. 4—		> 500 mm deep	29
Design capacity of end plate		14.2 Configuration B—Member	
(Shear, block shear)	16	< 500 mm deep	31
10.5 DESIGN CHECK NO. 5—Design		APPENDICES	
capacity of supported member		A Limcon software	35
web (At end plate)	17	B ASI Design Guide 4	
		comment form	39



LIST OF FIGURES

		<i>Page</i>			<i>Page</i>
Figure 1	Typical flexible end plate connections	2	Figure 13	Detailing limitations of design model	13
Figure 2	Uncoped and single web coped beam (end plate located towards top of beam)	3	Figure 14	End plate block shear areas in connection component	16
Figure 3	Uncoped and single web coped beam (end plate located towards bottom of beam)	3	Figure 15	Supported coped member—Critical section in bending	19
Figure 4	Double web coped beam (end plate depth matches remaining depth of web)	3	Figure 16	Connection parameters for beam rotation check	20
Figure 5	Erection aids	5	Figure 17	Local stability of SWC and DWC beams	21
Figure 6	Undercutting of web and distortion of end plate due to weld	5	Figure 18	Supporting members with supported members on one side	22
Figure 7	Behaviour of flexible end plate connection	6	Figure 19	Supporting members with supported members on two sides	23
Figure 8	Moment-rotation behaviour of flexible end plate connection	7	Figure 20	Single sided coped FEP connection to supporting UB	26
Figure 9	Shear stress distribution assumed ..	9	Figure 21	Geometry Configuration A—Member > 500 mm deep	29
Figure 10	Basis of design model	9	Figure 22	Geometry Configuration B—Member < 500 mm deep	31
Figure 11	Full depth end plates	10			
Figure 12	Connection geometry	11			

LIST OF TABLES

		<i>Page</i>			<i>Page</i>
Table 1	Flexible end plate design capacity table Configuration A—Member > 500 mm deep	30	Table 3	Flexible end plate design capacity table Configuration B—Member > 250 mm but < 350 mm deep	33
Table 2	Flexible end plate design capacity table Configuration B—Member > 350 mm but < 500 mm deep	32	Table 4	Flexible end plate design capacity table Configuration B—Member 200 mm deep	34

