Tubular Design Guide 21: Bolted bracing connections

by

P.W. Key and A.A. Syam

first edition - 2014



AUSTRALIAN STEEL INSTITUTE (ABN)/ACN (94) 000 973 839

Tubular Design Guide 21: Bolted bracing connections

Copyright © 2014 by AUSTRALIAN STEEL INSTITUTE

Published by: AUSTRALIAN STEEL INSTITUTE

All rights reserved. This book or any part thereof must not be reproduced in any form without the written permission of Australian Steel Institute.

Note to commercial software developers: Copyright of the information contained within this publication is held by Australian Steel Institute (ASI). Written permission must be obtained from ASI for the use of any information contained herein which is subsequently used in any commercially available software package.

FIRST EDITION 2014 (LIMIT STATES)

National Library of Australia Cataloguing-in-Publication entry:

Key, Peter W.

Tubular Design Guide 21: Bolted bracing connections / Peter W. Key, Arun A. Syam.

ISBN 978 1 921476 30 3 (pbk.).

Series: Structural steel tubular connection series.

Includes bibliographical references.

Steel, Structural - Standards - Australia.

Structural engineering.

Syam, Arun A.

Australian Steel Institute.

624.1821021894

Also in this series:

Tubular Design Guide 20: Background and design basis

Tubular Design Guide 22: Bolted bracing cleats

Tubular Design Guide 23: Plate fitments

Tubular Design Guide 24: Bolted planar connections

Tubular Design Guide 25: Fully welded – Simple planar connections Tubular Design Guide 26: Fully welded – Gap planar connections Tubular Design Guide 27: Fully welded – Overlap planar connections

Disclaimer: The information presented by the Australian Steel Institute in this publication has been prepared for general information only and does not in any way constitute recommendations or professional advice. While every effort has been made and all reasonable care taken to ensure the accuracy of the information contained in this publication, this information should not be used or relied upon for any specific application without investigation and verification as to its accuracy, suitability and applicability by a competent professional person in this regard. The Australian Steel Institute, its officers and employees and the authors and editors of this publication do not give any warranties or make any representations in relation to the information provided herein and to the extent permitted by law (a) will not be held liable or responsible in any way; and (b) expressly disclaim any liability or responsibility for any loss or damage costs or expenses incurred in connection with this publication by any person, whether that person is the purchaser of this publication or not. Without limitation, this includes loss, damage, costs and expenses incurred as a result of the negligence of the authors, editors or publishers.

The information in this publication should not be relied upon as a substitute for independent due diligence, professional or legal advice and in this regards the services of a competent professional person or persons should be sought.





CONTENTS

				Page					Page
Lis	t of	Figures	;	V			3.11.4	DESIGN CHECK NO. 4—	
List of Tables				vi				Design capacity of welds to	
Preface				viii				SSHS member	3-20
About the Authors				ix			3.11.5	DESIGN CHECK NO. 5—	
Ac	knov	wledger	nents	Х				Design capacity due to end	
								plate tearout in cleat plate	3-21
1	CONCEPT OF DESIGN GUIDES 1.1 Background			1-1			3.11.6	DESIGN CHECK NO. 6—	
				1-1				Design capacity of cleat	
	1.2	Include	ed connections	1-2				plate in block shear	3-23
							3.11.7	DESIGN CHECK NO. 7—	
2	TECHNICAL BASIS			2-1				Design capacity of cleat	
	2.1		ical background	2-1				plate in axial tension	3-25
		2.1.1	Technical basis	2-1			3.11.8	B DESIGN CHECK NO. 8—	
		2.1.2	Validity Limits	2-1				Design capacity of cleat	
		2.1.3	Design Capacity Factors	2-4				plate due to shear lag	3-26
	2.2	-	ties of connection elements	2-5			3.11.9	DESIGN CHECK NO. 9—	
		2.2.1	General	2-5				Design capacity of SSHS	
		2.2.2	Component material yield					member locally	3-28
			stress	2-5			3.11.1	0 DESIGN CHECK NO. 10—	
		2.2.3	SSHS material properties	2-6				Design capacity of bolts in	
		2.2.4	Design yield stress for	0.7			0.44.4	shear and ply bearing	3-30
		005	Australian produced SSHS	2-7			3.11.1	1 DESIGN CHECK NO. 11—	
		2.2.5	Design capacity of welds	2-7				Design capacity of welds to	0.04
	2.2	2.2.6	Design capacity of bolts ences for Sections 1 and 2	2-8			0 44 4	SSHS member	3-31
	2.3	Refere	ences for Sections 1 and 2	2-9			3.11.1	2 DESIGN CHECK NO. 12—	
2	CI C	TTED	SSHS END CONNECTION	2.4				Design capacity of cleat	2 22
3				3-1 3-1			2 4 4 4	plate due to shear lag 3 DESIGN CHECK NO. 13—	3-32
			ption of connection I detailing of connection	3-1			3.11.1		
			ng considerations	3-3 3-4				Design capacity of SSHS member locally	3-34
			round information	3-4			2 11 1	4 DESIGN CHECK NO. 14—	3-34
	5.4	3.4.1	Recent research	3-6			3.11.1	Design capacity of cleat plat	_
		3.4.2	Relevant international codes					under eccentric compression	
		J.T.Z	and specifications	3-7				force	3-35
	3.5	Compl	iance with AS 4100	0 7		3 13	2 Desig	ın example	3-38
	0.0		ements	3-9				n capacity tables	3-46
	36		of design model	3-11			4 Refer		3-60
			ation of design actions	3-13		• • •			0 00
			nmended design model-		4	WE	LDED	TEE SSHS END	
			ection notation	3-14			NNECT		4-1
	3.9	Recom	nmended design model—					ription of connection	4-1
			of validity	3-15				al detailing of connection	4-3
	3.10		nmended design model—					ing considerations	4-4
			ary of design checks	3-16				ground information	4-6
	3.11		nmended design model—				4.4.1	Recent research	4-6
		Gener	al	3-17			4.4.2	Relevant International	
		3.11.1	DESIGN CHECK NO. 1—					Codes and specifications	4-8
			Detailing requirements	3-17		4.5	Comp	liance with AS 4100	
		3.11.2	DESIGN CHECK NO. 2—					rements	4-9
			Validity limits and minimum			4.6	Basis	of design model	4-11
			design actions	3-18				lation of design actions	4-13
		3.11.3	DESIGN CHECK NO. 3—			4.8		mmended design model—	
			Design capacity of bolts in				Conn	ection notation	4-14
			shear and ply bearing	3-19					





			Page					Page
4.9	Recom	mended design model—				4.11.17	DESIGN CHECK NO. 17—	
		of validity	4-15				Design capacity of SSHS	
4.10		nmended design model—					wall—local crippling	4-43
	Summ	4-16			4.11.18	DESIGN CHECK NO. 18—		
4.11	Recon					Design capacity of cleat		
	Gener		4-17				plate under eccentric	
	4.11.1	DESIGN CHECK NO. 1—					compression force	4-45
		Detailing Requirements	4-17		4.12	Design	n example	4-48
	4.11.2	DESIGN CHECK NO. 2—			4.13	B Design	capacity tables	4-58
		Validity limits and minimum			4.14	Refere	nces	4-72
		design actions	4-18					
	4.11.3	DESIGN CHECK NO. 3—		5	FLA	TTENE	D END CHS CONNECTION	I 5-1
		Design capacity of bolts in			5.1	Descrip	otion of connection	5-1
		shear and bearing	4-19		5.2	Typical	detailing of connection	5-3
	4.11.4	DESIGN CHECK NO. 4—			5.3	Detailir	ng considerations	5-4
		Design capacity of welds			5.4	Backgr	ound information	5-6
		of cleat plate to cap plate	4-20			5.4.1	Recent research	5-6
	4.11.5	DESIGN CHECK NO. 5—				5.4.2	Relevant International	
		Design capacity due to end					Guidance documents	5-7
		plate tearout in cleat plate	4-22		5.5		ance with AS 4100	
	4.11.6	DESIGN CHECK NO. 6—				require		5-8
		Design capacity of cleat					of design model	5-10
		plate in block shear	4-24				ation of design actions	5-11
	4.11.7	DESIGN CHECK NO. 7—			5.8		mended design model—	
		Design capacity of cleat					ction notation	5-12
		plate in axial tension	4-26		5.9		mended design model—	
	4.11.8	DESIGN CHECK NO. 8—					of validity	5-13
		Design capacity of cap			5.10		nmended design model—	
		plate due to punching shear	4-27				ary of design checks	5-14
	4.11.9	DESIGN CHECK NO. 9—			5.11		mended design model—	
		Design capacity of cap plate				Genera		5-15
		due to plastic hinge formation				5.11.1	DESIGN CHECK NO. 1—	
		(cap + tube walls)	4-29				Detailing requirements	5-15
	4.11.10	DESIGN CHECK NO. 10—				5.11.2	DESIGN CHECK NO. 2—	
		Design capacity of cap					Validity limits and minimum	5 40
		plate due to plastic hinge	4.04			5 4 4 0	design actions	5-16
		formation (cap only)	4-31			5.11.3	DESIGN CHECK NO. 3—	
	4.11.11	DESIGN CHECK NO. 11 –					Design capacity of bolts in	- 4 -
		Design capacity of welds	4.00			E 44 4	shear and ply bearing	5-17
	1 1 1 1 1	of cap plate to SSHS	4-33			5.11.4	DESIGN CHECK NO. 4—	
	4.11.12	DESIGN CHECK NO. 12—					Design capacity due to end	E 10
		Design capacity of SSHS	4 2E			E 11 E	plate tearout in flattened end	5-10
	1 11 10	wall – local yielding BDESIGN CHECK NO. 13—	4-35			5.11.5	DESIGN CHECK NO. 5—	
	4.11.13	Design capacity of bolts					Design capacity of flattened end in block shear	5-19
		. ,	4-37			E 11 G	DESIGN CHECK NO. 6—	5-19
	1111/	in shear and ply bearing DESIGN CHECK NO. 14—	4-37			5.11.6		
	4.11.14	Design capacity of welds					Design capacity of flattened end in axial tension	5-21
		of cleat plate to cap plate	4-38			5 11 7	DESIGN CHECK NO. 7—	J-Z I
	1 11 15	DESIGN CHECK NO. 15—	4-30			5.11.7	Design capacity of bolts in	
	4.11.10						shear and bearing	5-22
		Design capacity of welds of cap plate to SSHS	4-40			5 11 Ω	DESIGN CHECK NO. 8—	J-22
	A 11 16	DESIGN CHECK NO. 16—				0.11.0	Design capacity of flattened	
	- - 1 1 . 1 C	Design capacity of SSHS					end under eccentric	
		wall—local yielding	4-42				compression force	5-23
		wan local yiciding	7 74		5 12	Design	example	5-26
					J. 12			





	Page		Page
5.13 Design capacity tables 5.14 References	5-33 5-37	APPENDIX B—ASI Design Guide 21 comment form	8-1
6 NOTATION AND ABBREVIATIONS	6-1		
APPENDIX A—Limcon Design Example Output	7-1		

LIST OF FIGURES

		H	Page			Page
Figure	1.1	Connections included in this		Figure 4.6	Failure modes involving	
		Design Guide	1-2		cap plate	4-7
Figure	2.1	Definition of element width		•	Eccentricities at cleats	4-9
		for RHS flanges	2-3	Figure 4.8	Design actions at	
Figure	3.1	Typical slotted SSHS end			connection	4-13
		connection configurations	3-1	Figure 4.9	Notation for single cleat	
Figure	3.2	Example of forked SSHS end			plate	4-14
		connection configuration	3-2	Figure 4.10	Notation for forked cleat	
Figure	3.3	Single and double line of bolts	3		plate	4-14
		to single cleat plate: CHS,		Figure 4.11	Stress distribution through	
		SHS and RHS members	3-3		cap plate to cleat plate	4-21
Figure		Edge distances for bolt holes	3-5	Figure 4.12	Detailing of bolt hole edge	
Figure	3.5	Fabrication types for slotted			distances	4-23
		end plate connections	3-6	Figure 4.13	Cleat plate block shear areas	
Figure		Eccentricities at cleats	3-9		in connection component	4-25
Figure	3.7	Design actions at	0.40	•	Punching shear in cap plate	4-28
-	0 0		3-13	Figure 4.15	Geometry defining hinges	
Figure	3.8	Notation for single cleat	0.44		in cap plate and hollow	4 00
-	0 0	•	3-14	E'	section walls	4-30
Figure	3.9	Notation for forked cleat	0.44	Figure 4.16	Geometry defining hinges	4 00
- :	0.40	•	3-14	C: 4 47	in cap plate only	4-32
Figure	3.10	Minimum edge distances	2 22	Figure 4.17	Dispersion of stress through	1 2 1
Ciaura	2 11	•	3-22	Ciguro 4 10	to weld of cap plate to SSHS	4-34
rigure	3.11	End plate block shear areas	3-24	rigure 4.16	Definition of effective length of SSHS wall	4-36
Eiguro	2 12	in connection component Effective length of cleat	3-24	Figure 4.10	Dispersion of stress through	4-30
i igui e	3.12		3-36	rigure 4.19	cap plate to cap plate to	
Figure	2 12	Details and behaviour of	0-30		cleat plate weld	4-39
i igui e	5.15		3-37	Figure 4 20	Dispersion of stress through	4-55
Figure	3 14	Design example	0 01	1 iguic 4.20	cap plate to cap plate to	
i iguic	0.14		3-38		SSHS weld	4-41
Figure	3 15	Assumed cleat assembly	0 00	Figure 4 21	Dispersion of stress through	
9			3-45	9	cap plate to SSHS wall	4-42
Figure	4.1	Typical welded tee end		Figure 4.22	Dispersion of stress through	
		connection configurations	4-1	9	cap plate to SSHS wall	4-44
Figure	4.2	Typical forked tee end		Figure 4.23	Effective length of cleat	
J		connection configuration	4-2	J	assembly	4-46
Figure	4.3	Single and double line of bolts	3	Figure 4.24	Details and behaviour of	
Ū		to single cleat plate: CHS,		J	forked plate model	4-47
		SHS and RHS members	4-3	Figure 4.25	Design example	
Figure	4.4	Edge distances for bolt holes	4-5	<u> </u>	configuration—welded	
Figure	4.5	Stress distribution through			tee end	4-48
		cap plate	4-7	Figure 4.26	Assumed cleat assembly	
					dimensions	4-57





Figure 5.1	Typical flattened end CHS configurations	5-1	Figure 5.9 End plate block tear out areas in flattened end	5-20
Figure 5.2	Various forms of end	5-2	Figure 5.10 Effective length of	5-25
Figure 5.3	-		Figure 5.11 Effective length of cleat	
Figure 5.4	bolts to end flattened CHS Edge distances for bolt holes	5-3 5-5	assembly 5 Figure 5.12 Design example	5-25
Figure 5.5		5-8		5-26
Figure 5.6		5-11	Figure 5.13 Geometry of assumed	
Figure 5.7	Notation for flattened end			5-32
	CHS	5-12		
Figure 5.8	Minimum edge distances for bolt holes in end plate	5-18		
	119	ST OF	TABLES	
	LIC	Page		Page
Table 2.1	Pationalised validity limits	J		J
	Rationalised validity limits SSHS bracing connections	2-2	Table 3.13.3(a) Slotted end plate connection axial design capacity – 'small' SHS –	
	Section slenderness limits to	2 2		3-52
	4100 and Eurocode 3	2-3	Table 3.13.3(b) Slotted end plate connection	- 0
	Section slenderness limits to		axial design capacity – 'large' SHS –	
Eur	ocode 3 for design Grades		Grade 350	3-53
) 250, 350 and 450 MPa	2-4	Table 3.13.4(a) Slotted end plate connection	
	Minimum plate material		axial design capacity – 'small' SHS –	
	perties to AS/NZS 3678	2-5		3-54
	Strength of flat bars to NZS 3679.1 Grade 300	2.6	Table 3.13.4(b) Slotted end plate connection	
	Minimum SSHS material	2-6	axial design capacity – 'large' SHS – Grade 450	3-55
	perties to AS/NZS 1163	2-6	Table 3.13.5(a) Slotted end plate connection	
	Design yield stress for SSHS	_ •	axial design capacity – 'small' RHS –	
	ted failure modes for SSHS to			3-56
AS/	NZS 1163	2-7	Table 3.13.5(b) Slotted end plate connection	
	Strength limit state design		axial design capacity – 'large' RHS –	
•	acities of equal leg fillet welds			3-57
•	unit length Category SP,		Table 3.13.6(a) Slotted end plate connection	
φ = ≥3 r	0.8, $k_r = 1.0$, material thickness	2-7	axial design capacity – 'small' RHS – Grade 450	3-58
	Strength limit state high strength	2-1	Table 3.13.6(b) Slotted end plate connection	
	ictural bolts 8.8/S, 8.8/TB, 8.8/TF	:	axial design capacity – 'large' RHS –	
	ing categories (f _{uf} = 830 MPa)	2-8		3-59
	Rationalised validity limits for		Table 4.1 Rationalised validity limits for	
slot	ted SSHS end connection	3-15	welded tee end connection	4-15
	1(a) Slotted end plate connection		Table 4.13.1(a) Welded tee SSHS end	
	al design capacity – 'small' CHS		connection – axial design capacity	4 00
	ide 250	3-48		4-60
	1(b) Slotted end plate connectic al design capacity – 'large' CHS -		Table 4.13.1(b) Welded tee SSHS end connection – axial design capacity	
	ide 250	3-49		4-61
	2(a) Slotted end plate connection		Table 4.13.2(a) Welded tee SSHS end	
	al design capacity – 'small' CHS		connection – axial design capacity	
	ade 350	3-50		4-62
Table 3.13.2	2(b) Slotted end plate connection	n	Table 4.13.2(b) Welded tee SSHS end	
	al design capacity – 'large' CHS -		connection – axial design capacity	
Gra	ide 350	3-51	'large' CHS – Grade 350	4-63

Page



Page

	Page		Page
Table 4.13.3(a) Welded tee SSHS end connection – axial design capacity		Table 4.13.5(b) Welded tee SSHS end connection – axial design capacity	
'small' SHS – Grade 350	4-64	'large' RHS – Grade 350	4-69
Table 4.13.3(b) Welded tee SSHS end		Table 4.13.6(a) Welded tee SSHS end	
connection – axial design capacity		connection – axial design capacity	
'large' SHS – Grade 350	4-65	'small' RHS – Grade 450	4-70
Table 4.13.4(a) Welded tee SSHS end		Table 4.13.6(b) Welded tee SSHS end	
connection – axial design capacity		connection – axial design capacity	
'small' SHS – Grade 450	4-66	'large' RHS – Grade 450	4-71
Table 4.13.4(b) Welded tee SSHS end		Table 5.1 Rationalised validity limits for	
connection – axial design capacity		flattened end CHS connection	5-13
'large' SHS – Grade 450	4-67	Table 5.13.1 Flattened end CHS connection	n
Table 4.13.5(a) Welded tee SSHS end		axial design capacity – Grade 250	5-34
connection – axial design capacity		Table 5.13.2 Flattened end CHS connection	n
'small' RHS – Grade 350	4-68	axial design capacity - Grade 350	5-35





PREFACE

This new series of connection publications by the Australian Steel Institute (ASI) covering design capacity tables, theory and design of individual structural steel hollow section ('tubular') member connections will be known as the Structural Steel Tubular Connection Series: 1st edition 2013 ('Tubular Connection Series'). The Tubular Connection Series details the method of design and provides design capacity tables and detailing parameters for a range of tubular connections commonly used in Australia. Connections have a major engineering and economic importance in steel structures influencing design, detailing, fabrication and erection costs. Standardisation of design approach integrated with industry detailing is the key to minimum costs at each stage. The Tubular Connection Series is written in the same format as and extends the range of the existing 'Structural Steel Connection Series Parts 1 and 2' published by ASI commencing 2007. Each book in the new Tubular Connection Series is numbered as a continuation from the existing series and hence this current book is referred to as 'Tubular Design Guide 21' (TDG21). The Tubular Connection Series replaces and enhances an AISC publication released in 1996 and titled 'Design of structural steel hollow section connections' (often referred to as the 'Blue Book'). With significant international research undertaken in the interim period and new and refined design models available, together with improvements in the performance of Australian produced structural steel hollow sections (SSHS), the time was appropriate to revise and update the Blue Book.

Tubular Design Guide 21 brings together a number of design models for end connections associated with bracing members in frames that are usually subjected to predominantly axial tension and/or compression and are pin-ended. The format and intent of the technical components of TDG21 is to provide sufficient technical basis to allow TDG21 to be a selfstanding document, but at the same time, where substantive background technical basis is required, the reader may refer back to both Tubular Design Guide 20 (TDG20) and Handbook 1 of the existing Structural Steel Connection Series.

This has been achieved through extensive local and international literature reviews using ASI's close association with like organisations and searching the wealth of material contained in the ASI Library (the largest steel design library in the Southern Hemisphere). This process consolidated industry best practice, references and research papers. TDG21, in conjunction with TDG20 and Handbook 1, formulates the design models and procedures for the assessment of bolts, bolt groups, welds, weld groups, connection components and supporting members associated with the end connections to SSHS bracing members.

Following on from the existing Structural Steel Connection Series, the new Tubular Connection Series format, with separate design guides for individual connection types or groupings related to similar functions, is intended to facilitate addition to, or revision of, connection model theory using relevant new local or international research. Connection models developed follow a stylised page format with a numbered DESIGN CHECK procedure to simplify connection design capacity assessment. Combined with a worked example and accompanying design capacity tables, each connection model provides a self-standing solution for the design engineer.

Engineering Systems has worked closely with the ASI to further develop their existing Limcon software as the companion program for this new Tubular Connection Series. The latest version of Limcon (V3.6) fully implements the new connection design models and was employed in checking the design tables. The Limcon output for one or more of the worked examples is included in an appendix to each design guide for each connection design type. The program is an efficient tool covering the full range of structural connections, including those beyond the scope of the design capacity tables provided in the Tubular Connection Series.

The existing Structural Steel Connection Series included comment/feedback forms. In the current series, these are replaced by a recently developed web based eForum facility. Every publication, seminar and talk that ASI sponsors has or will have a corresponding thread on the ASI eForum. Users are encouraged to log into the eForum and provide feedback on this current series. The eForum is located off our website at http://steel.org.au/forum/

> P.W. Kev A.A. Syam

> > viii



