Tubular Design Guide 23: Plate fitments

by

P.W. Key and A.A. Syam

first edition - 2014



AUSTRALIAN STEEL INSTITUTE (ABN)/ACN (94) 000 973 839

Tubular Design Guide 23: Plate fitments

Copyright © 2014 by AUSTRALIAN STEEL INSTITUTE

Published by: AUSTRALIAN STEEL INSTITUTE

All rights reserved. This book or any part thereof must not be reproduced in any form without the written permission of Australian Steel Institute.

Note to commercial software developers: Copyright of the information contained within this publication is held by Australian Steel Institute (ASI). Written permission must be obtained from ASI for the use of any information contained herein which is subsequently used in any commercially available software package.

FIRST EDITION 2014 (LIMIT STATES)

National Library of Australia Cataloguing-in-Publication entry:

Key, Peter W.

Tubular Design Guide 23: Plate fitments / Peter W. Key, Arun A. Syam.

ISBN 978 1 921476 32 7 (pbk.).

Series: Structural steel tubular connection series.

Includes bibliographical references.

Steel, Structural—Standards - Australia.

Structural engineering.

Svam. Arun A.

Australian Steel Institute.

624.1821021894

Also in this series:

Tubular Design Guide 20: Background and design basis Tubular Design Guide 21: Bolted bracing connections Tubular Design Guide 22: Bolted bracing cleats Tubular Design Guide 24: Bolted planar connections Tubular Design Guide 25: Fully welded—Simple planar of

Tubular Design Guide 25: Fully welded—Simple planar connections Tubular Design Guide 26: Fully welded—Gap planar connections Tubular Design Guide 27: Fully welded—Overlap planar connections

Disclaimer: The information presented by the Australian Steel Institute in this publication has been prepared for general information only and does not in any way constitute recommendations or professional advice. While every effort has been made and all reasonable care taken to ensure the accuracy of the information contained in this publication, this information should not be used or relied upon for any specific application without investigation and verification as to its accuracy, suitability and applicability by a competent professional person in this regard. The Australian Steel Institute, its officers and employees and the authors and editors of this publication do not give any warranties or make any representations in relation to the information provided herein and to the extent permitted by law (a) will not be held liable or responsible in any way; and (b) expressly disclaim any liability or responsibility for any loss or damage costs or expenses incurred in connection with this publication by any person, whether that person is the purchaser of this publication or not. Without limitation, this includes loss, damage, costs and expenses incurred as a result of the negligence of the authors, editors or publishers.

The information in this publication should not be relied upon as a substitute for independent due diligence, professional or legal advice and in this regards the services of a competent professional person or persons should be sought.





CONTENTS

| | Page | | | | Page |
|---------------------------------------|------|---|-------------|-----------------------------|------|
| List of Figures | ٧ | | 3.11.5 | DESIGN CHECK NO. 5— | |
| List of Tables | V | | | Design capacity of web side | |
| Preface | vii | | | plate in shear | 3-20 |
| About the Authors | viii | | 3.11.6 | DESIGN CHECK NO. 6— | |
| Acknowledgements | ix | | | Design capacity of web side | |
| Ğ | | | | plate in block shear | 3-21 |
| 1 CONCEPT OF DESIGN GUIDES | 1-1 | | 3.11.7 | DESIGN CHECK NO. 7— | |
| 1.1 Background | 1-1 | | | Design capacity of web side | |
| 1.2 Included connections | 1-2 | | | plate in bending | 3-23 |
| | | | 3.11.8 | DESIGN CHECK NO. 8— | |
| 2 TECHNICAL BASIS | 2-1 | | | Design capacity of SSHS | |
| 2.1 Technical background | 2-1 | | | member—local shear | 3-24 |
| 2.1.1 Technical basis | 2-1 | | 3.11.9 | DESIGN CHECK NO. 9— | |
| 2.1.2 Validity limits | 2-1 | | | Design capacity of SSHS | |
| 2.1.3 Design capacity factors | 2-4 | | | member—punching shear | 3-25 |
| 2.2 Properties of connection elements | 2-5 | | 3.11.10 | DESIGN CHECK NO. 10— | |
| 2.2.1 General | 2-5 | | | Design capacity of SSHS | |
| 2.2.2 Component material | | | | member—face yielding | 3-26 |
| design yield stress | 2-5 | | 3.12 Design | • • | 3-27 |
| 2.2.3 SSHS material properties | 2-6 | | - | n capacity tables | 3-32 |
| 2.2.4 Design yield stress for | | | 3.14 REFEI | | 3-53 |
| Australian produced SSHS | 2-7 | | 0 <u>.</u> | | 0 00 |
| 2.2.5 Design capacity of welds | 2-7 | 4 | MOMENT S | SIDE PLATE | 4-1 |
| 2.2.6 Design capacity of bolts | 2-8 | • | | ption of connection | 4-1 |
| 2.3 References for Sections 1 and 2 | 2-9 | | | I detailing of connection | 4-3 |
| 2.0 References for economic Fana 2 | 20 | | | ng considerations | 4-4 |
| 3 WEB SIDE PLATE | 3-1 | | | round information | 4-5 |
| 3.1 Description of connection | 3-1 | | • | iance with AS 4100 | . 0 |
| 3.2 Typical detailing of connection | 3-2 | | | ements | 4-6 |
| 3.3 Detailing considerations | 3-3 | | • | of design model | 4-7 |
| 3.4 Background information | 3-5 | | | ation of design actions | 4-8 |
| 3.4.1 Recent research | 3-5 | | | mended design model— | . 0 |
| 3.4.2 Relevant international | 00 | | | ection notation | 4-9 |
| codes and specifications | 3-5 | | | mended design model— | . 0 |
| 3.5 Compliance with AS 4100 | 00 | | | of validity | 4-10 |
| requirements | 3-6 | | | nmended design model— | 1 10 |
| 3.6 Basis of design model | 3-7 | | | ary of design checks | 4-11 |
| 3.7 Calculation of design actions | 3-10 | | | nmended design model— | |
| 3.8 Recommended design model— | 0.0 | | | nnection forces | 4-12 |
| Connection notation | 3-11 | | | DESIGN CHECK NO. 1— | – |
| 3.9 Recommended design model— | 0 | | | Detailing requirements | 4-12 |
| Limits of validity | 3-12 | | 4.11.2 | DESIGN CHECK NO. 2— | |
| 3.10 Recommended design model— | 0 .2 | | | Validity limits and minimum | |
| Summary of design checks | 3-13 | | | design actions | 4-13 |
| 3.11 Recommended design model | 3-14 | | 4 11 3 | DESIGN CHECK NO. 3— | 0 |
| 3.11.1 DESIGN CHECK NO. 1— | 0 | | | Design capacity of welds to | |
| Detailing requirements | 3-14 | | | SSHS member | 4-14 |
| 3.11.2 DESIGN CHECK NO. 2— | • | | 4.11.4 | DESIGN CHECK NO. 4— | |
| Validity limits and minimum | | | | Design capacity of SSHS | |
| design actions | 3-16 | | | member locally—chord face | |
| 3.11.3 DESIGN CHECK NO. 3— | 5 .0 | | | yielding | 4-16 |
| Design capacity of bolts in | | | 4.11.5 | DESIGN CHECK NO. 5— | |
| shear and ply bearing | 3-17 | | | Design capacity of SSHS | |
| 3.11.4 DESIGN CHECK NO. 4— | | | | member locally—punching | |
| Design capacity of welds to | | | | shear | 4-19 |
| SSHS member | 3-19 | | | | . • |



Page Page 4.11.6 DESIGN CHECK NO. 6-5.11.5 DESIGN CHECK NO. 5-Design capacity of SSHS Design capacity of SSHS member locally—face shear 4-20 member locally—face DESIGN CHECK NO. 7-4.11.7 yielding 5-20 5.11.6 DESIGN CHECK NO. 6-Design capacity of side plate-section yield 4-21 Design capacity of SSHS 4.12 Design example 4-23 member locally—face 4.13 Design capacity tables 4-26 punching shear 5-22 4.14 References 4-38 5.11.7 DESIGN CHECK NO. 7— Design capacity of SSHS member locally-chord 5 TRANSVERSE PLATE 5-1 side wall failure 5.1 Description of connection 5-1 5-24 5.2 Typical detailing of connection 5-2 5.11.8 DESIGN CHECK NO. 8-5.3 Detailing considerations 5-3 Design capacity of transverse 5.4 Background information 5-5 plate in axial compression 5.4.1 Recent research 5-5 (effective width) 5-26 Relevant international 5.11.9 DESIGN CHECK NO. 9-5.4.2 codes and specifications 5-6 Design capacity of weld 5.5 Compliance with AS 4100 to SSHS member 5-27 requirements 5-7 5.11.10 DESIGN CHECK NO. 10-5.6 Basis of design model Design capacity of SSHS 5-9 5.7 Calculation of design actions member locally-face 5-11 5.8 Recommended design model yielding 5-28 5.11.11 DESIGN CHECK NO. 11-Connection notation 5-12 5.9 Recommended design model— Design capacity of SSHS Limits of validity 5-13 member locally-face 5.10 Recommended design model punching shear 5-30 Summary of design checks 5-14 5.11.12 DESIGN CHECK NO. 12-5.11 Recommended design model— Design capacity of SSHS General 5-15 member locally-chord 5.11.1 DESIGN CHECK NO. 1side wall failure 5-31 5-33 **Detailing requirements** 5-15 5.12 Design example 5.11.2 DESIGN CHECK NO. 2-5.13 Design capacity tables 5-36 Validity limits and minimum 5.14 References 5-60 design actions 5-16 5.11.3 DESIGN CHECK NO. 3-6 NOTATION AND ABBREVIATIONS 6-1 Design capacity of transverse plate in axial tension **APPENDICES** (effective width) 5-17 A—Limcon design example output 7-1 5.11.4 DESIGN CHECK NO. 4-ASI Design Guide 23 Design capacity of weld to Comment form 8-1 SSHS member 5-19





LIST OF FIGURES

| | | Page | | | Page | | |
|----------------------------|--|--------------|---------------------------|--|--------------|--|--|
| Figure 1.1 | Connections included in this Design Guide | 1-2 | Figure 4.3 | Typical detailing of moment side plate | 4-3 | | |
| Figure 2.1 | Definition of element width for F flanges | | Figure 4.4 Figure 4.5 | Nominal connection eccentricity Connection component design | | | |
| Figure 3.1 | Typical web side plate configurations | 3-1 | Figure 4.6 | actions Notation for moment side plate | 4-8 4-9 | | |
| Figure 3.2 | Single and double line of bolts | | Figure 4.7 | Side plate weld design actions | 4-15 | | |
| Figure 3.3 | to single web side plate Edge distances for bolt holes | 3-2 3-3 | Figure 4.8 | Assumed critical section for side plate | 4-22 | | |
| Figure 3.4 | Examples of 'flexible' and 'stiff' support conditions | 3-6 | Figure 4.9 Figure 4.10 | Design example configuration Standardised moment side | 4-23 | | |
| Figure 3.5 | Bolt group stiff support design eccentricity | 3-7 | Figure 5.1 | plate Typical transverse plate | 4-26 | | |
| Figure 3.6 | Short web side plate— Limitations | 3-9 | Figure 5.2 | configurations for SSHS Single and double line of bolts | 5-1 | | |
| Figure 3.7 | Connection component | | riguic o.z | to single transverse plate | | | |
| Figure 3.8 | design actions Notation for web side plate | 3-10 3-11 | | connected to face of support: CHS, SHS and RHS members | 5-2 | | |
| Figure 3.9 | Minimum clearance between support and member | 3-16 | Figure 5.3 Figure 5.4 | Edge distances for bolt holes Eccentricities at cleats | 5-4 5-7 | | |
| Figure 3.10 | Block shear capacity areas— Web side plate | 3-23 | Figure 5.5 Figure 5.6 | Design actions at connection Notation for transverse plate | 5-11 | | |
| Figure 3.11 Figure 3.12 | Design example configuration Standardised web side plate | 3-27 3-28 | Figure 5.7 | design model Effective width of transverse | 5-12 | | |
| Figure 4.1 | Typical moment side plate configurations for SSHS | 0 _0 | Figure 5.8 | plate Design example configuration | 5-18 5-33 | | |
| Figure 4.0 | sections | 4-1 | Figure 5.9 | Standardised transverse plate | 5-36 | | |
| Figure 4.2 | Typical moment side plate configuration for slotted | | | | | | |
| | through connection | 4-2 | | | | | |
| LIST OF TABLES | | | | | | | |
| | | Page | | length Category SP, φ = 0.8, 1.0, material thickness ≥3 mm | 2-8 | | |
| | Rationalised validity limits for IS bracing connections | 2-2 | ^ r - | | Page | | |
| Table 2.2 S | Section slenderness limits to | | | Strength limit state high strength | | | |
| | 4100 and Eurocode 3 Section slenderness limits to | 2-3 | bolti | ctural bolts 8.8/S, 8.8/TB, 8.8/TF ng categories (f_{uf} = 830 MPa) | 2-8 | | |
| | ocode 3 for design grades 250, 350 and 450 MPa | 2-4 | | Component design actions | 3-7 | | |



Table 2.4 Minimum plate material

Table 2.5 Strength of flat bars to

AS/NZS 1163

Table 2.6 Minimum SSHS material

properties to AS/NZS 3678

AS/NZS 3679.1 Grade 300

properties to AS/NZS 1163

related failure modes for SSHS to

capacities of equal leg fillet welds per

Table 2.7 Design yield stress for SSHS

Table 2.8 Strength limit state design



2-5

2-6

2-6

2-7

Table 3.2 Rationalised validity limits for

web side plate connection

- 'small' CHS - Grade 250

Table 3.13.1(a) Web side plate design capacity

Table 3.13.1(b) Web side plate design capacity - 'large' CHS - Grade 250; $n_q = 1$

Table 3.13.1(c) Web side plate design capacity

Table 3.13.2(a) Web side plate design capacity

Table 3.13.2(b) Web side plate design capacity - 'large' CHS - Grade 350; $n_q = 1$

- 'small' CHS - Grade 350

- 'large' CHS - Grade 250; $n_g = 2$

3-12

3-34

3-35

3-35

3-36

3-37

| Table 3.13.2(c) Web side plate design capacity | Page |
|--|---|
| - 'large' CHS - Grade 350; $n_g = 2$ 3-38 Page | Table 4.13.4 Moment side plate design capacity - SHS - Grade 450 4-32 |
| Table 3.13.3(a) Web side plate design capacity | Table 4.13.5 Moment side plate design capacity |
| - 'small' SHS - Grade 350 3-39 | - RHS - Grade 350 4-34 |
| Table 3.13.3(b) Web side plate design capacity | Table 4.13.6 Moment side plate design capacity |
| - 'large' SHS - Grade 350; $n_g = 1$ 3-41 | - RHS - Grade 450 4-36 |
| Table 3.13.3(c) Web side plate design capacity | Table 5.1 Rationalised validity limits for |
| - 'large' SHS - Grade 350; $n_g = 2$ 3-42 | transverse plate connection 5-13 |
| Table 3.13.4(a) Web side plate design capacity | Table 5.13.1(a) Transverse plate tension |
| - 'small' SHS – Grade 4503-43 | capacity (ΦN_t) – CHS – Grade 250 5-38 |
| Table 3.13.4(b) Web side plate design capacity | Table 5.13.1(b) Transverse plate compression |
| – 'large' SHS – Grade 450; $n_g = 1$ 3-45 | capacity (ΦN _c) – CHS – Grade 250 5-39 |
| Table 3.13.4(c) Web side plate design capacity | Table 5.13.2(a) Transverse plate tension |
| - 'large' SHS - Grade 450; $n_q = 2$ 3-46 | capacity (ΦN_t) – CHS – Grade 350 5-40 |
| Table 3.13.5(a) Web side plate design capacity | Table 5.13.2(b) Transverse plate compression |
| - 'small' RHS - Grade 350 3-47 | capacity (ΦN_c) – CHS – Grade 350 5-42 |
| Table 3.13.5(b) Web side plate design capacity | Table 5.13.3(a) Transverse plate tension |
| - 'large' RHS - Grade 350; $n_{q} = 1$ 3-48 | capacity (ΦN_t) – SHS – Grade 350 5-44 |
| Table 3.13.5(c) Web side plate design capacity | Table 5.13.3(b) Transverse plate compression |
| - 'large' RHS - Grade 350; $n_{q} = 2$ 3-49 | capacity (ΦN_c) – SHS – Grade 350 5-46 |
| Table 3.13.6(a) Web side plate design capacity | Table 5.13.4(a) Transverse plate tension |
| - 'small' RHS - Grade 450 3-50 | capacity (ΦN_t) – SHS – Grade 450 5-48 |
| Table 3.13.6(b) Web side plate design capacity | Table 5.13.4(b) Transverse plate compression |
| - 'large' RHS - Grade 450; $n_0 = 1$ 3-51 | capacity (ΦN_c) – SHS – Grade 450 5-50 |
| Table 3.13.6(c) Web side plate design capacity | Table 5.13.5(a) Transverse plate tension |
| - 'large' RHS – Grade 450; $n_q = 2$ 3-52 | capacity (ΦN_t) – RHS – Grade 350 5-52 |
| Table 4.1 Rationalised validity limits for | Table 5.13.5(b) Transverse plate compression |
| moment side plate connection 4-10 | capacity (ΦN_c) – RHS – Grade 350 5-54 |
| Table 4.13.1 Moment side plate design capacity | Table 5.13.6(a) Transverse plate tension |
| – CHS – Grade 250 4-27 | · · · |
| | . , , |
| Table 4.13.2 Moment side plate design capacity | Table 5.13.6(b) Transverse plate compression |
| - CHS - Grade 350 4-28 | capacity (ΦN_c) – RHS – Grade 450 5-58 |
| Table 4.13.3 Moment side plate design capacity | |
| – SHS – Grade 350 4-30 | |





PREFACE

This new series of connection publications by the Australian Steel Institute (ASI) covering design capacity tables, theory and design of individual structural steel hollow section ('tubular') member connections will be known as the Structural Steel Tubular Connection Series: 1st edition 2013 ('Tubular Connection Series'). The Tubular Connection Series details the method of design and provides design capacity tables and detailing parameters for a range of tubular connections commonly used in Australia. Connections have a major engineering and economic importance in steel structures influencing design, detailing, fabrication and erection costs. Standardisation of design approach integrated with industry detailing is the key to minimum costs at each stage. The Tubular Connection Series is written in the same format as and extends the range of the existing 'Structural Steel Connection Series Parts 1 and 2' published by ASI commencing 2007. Each book in the new Tubular Connection Series is numbered as a continuation from the existing series and hence this current book is referred to as 'Tubular Design Guide 23' (TDG23). The Tubular Connection Series replaces and enhances an AISC publication released in 1996 and titled 'Design of structural steel hollow section connections' (often referred to as the 'Blue Book'). With significant international research undertaken in the interim period and new and refined design models available, together with improvements in the performance of Australian produced structural steel hollow sections (SSHS), the time was appropriate to revise and update the Blue Book.

Tubular Design Guide 23 brings together a number of design models for plate fitments that are connected directly to SSHS members and may act as intermediate components in connections. The format and intent of the technical components of TDG23 is to provide sufficient technical basis to allow TDG23 to be a self-standing document, but at the same time, where substantive background technical basis is required, the reader may refer back to both Tubular Design Guide 20 (TDG20) and Handbook 1 of the existing Structural Steel Connection Series.

This has been achieved through extensive local and international literature reviews using ASI's close association with like organisations and searching the wealth of material contained in the ASI Library (the largest steel design library in the Southern Hemisphere). This process consolidated industry best practice, references and research papers. TDG23, in conjunction with TDG20 and Handbook 1, formulates the design models and procedures for the assessment of plate fitments to SSHS members.

Following on from the existing Structural Steel Connection Series, the new Tubular Connection Series format, with separate design guides for individual connection types or groupings related to similar functions, is intended to facilitate addition to or revision of connection model theory using relevant new local or international research. Connection models developed follow a stylised page format with a numbered DESIGN CHECK procedure to simplify connection design capacity assessment. Combined with a worked example and accompanying design capacity tables, each connection model provides a self-standing solution for the design engineer.

Engineering Systems has worked closely with the ASI to further develop their existing Limcon software as the companion program for this new Tubular Connection Series. The latest version of Limcon (V3.6) fully implements the new connection design models and was employed in checking the design tables. The Limcon output for one or more of the worked examples is included in an appendix to each design guide for each connection design type. The program is an efficient tool covering the full range of structural connections, including those beyond the scope of the design capacity tables provided in the Tubular Connection Series.

The existing Structural Steel Connection Series included comment/feedback forms. In the current series, these are replaced by a recently developed web based eForum facility. Every publication, seminar and talk that ASI sponsors has or will have a corresponding thread on the ASI eForum. Users are encouraged to log into the eForum and provide feedback on this current series. The eForum is located off our website at http://steel.org.au/forum/

P.W. Key A.A. Syam



