

**Tubular Design Guide 24:  
Bolted planar connections**

**by**

**P.W. Key**

**and**

**A.A. Syam**

**first edition – 2014**



AUSTRALIAN STEEL INSTITUTE  
(ABN)/ACN (94) 000 973 839

**Tubular Design Guide 24:  
Bolted planar connections**

Copyright © 2014 by AUSTRALIAN STEEL INSTITUTE

Published by: AUSTRALIAN STEEL INSTITUTE

All rights reserved. This book or any part thereof must not be reproduced in any form without the written permission of Australian Steel Institute.

*Note to commercial software developers: Copyright of the information contained within this publication is held by Australian Steel Institute (ASI). Written permission must be obtained from ASI for the use of any information contained herein which is subsequently used in any commercially available software package.*

FIRST EDITION 2014 (LIMIT STATES)

National Library of Australia Cataloguing-in-Publication entry:

Key, Peter W.

Tubular Design Guide 24: Bolted planar connections / Peter W. Key, Arun A. Syam

ISBN 9781921476334 (pbk.).

Series: Structural steel tubular connection series.

Includes bibliographical references.

Steel, Structural—Standards – Australia.

Structural engineering.

Syam, A. Arun.

Australian Steel Institute.

624.1821021894

Also in this series:

Tubular Design Guide 20: Background and design basis

Tubular Design Guide 21: Bolted bracing connections

Tubular Design Guide 22: Bolted bracing cleats

Tubular Design Guide 23: Plate fitments

Tubular Design Guide 25: Fully welded—Simple planar connections

Tubular Design Guide 26: Fully welded—Gap planar connections

Tubular Design Guide 27: Fully welded—Overlap planar connections

**Disclaimer:** The information presented by the Australian Steel Institute in this publication has been prepared for general information only and does not in any way constitute recommendations or professional advice. While every effort has been made and all reasonable care taken to ensure the accuracy of the information contained in this publication, this information should not be used or relied upon for any specific application without investigation and verification as to its accuracy, suitability and applicability by a competent professional person in this regard. The Australian Steel Institute, its officers and employees and the authors and editors of this publication do not give any warranties or make any representations in relation to the information provided herein and to the extent permitted by law (a) will not be held liable or responsible in any way; and (b) expressly disclaim any liability or responsibility for any loss or damage costs or expenses incurred in connection with this publication by any person, whether that person is the purchaser of this publication or not. Without limitation, this includes loss, damage, costs and expenses incurred as a result of the negligence of the authors, editors or publishers.

The information in this publication should not be relied upon as a substitute for independent due diligence, professional or legal advice and in this regards the services of a competent professional person or persons should be sought.



# CONTENTS

	<i>Page</i>		<i>Page</i>
Table of Figures	v	3.11.3 DESIGN CHECK NO. 3—	
List of Tables	iv	Design capacity of bolts in	
Preface	vii	axial tension	3-21
About the Authors	viii	3.11.4 DESIGN CHECK NO. 4—	
Acknowledgements	ix	Design capacity of welds to	
		SSHS member	3-22
1 CONCEPT OF DESIGN GUIDES	1-1	3.11.5 DESIGN CHECK NO. 5—	
1.1 Background	1-1	Design capacity of end plate	
1.2 Included connections	1-2	in bending	3-23
2 TECHNICAL BASIS	2-1	3.11.6 DESIGN CHECK NO. 6—	
2.1 Technical background	2-1	Design capacity due to local	
2.1.1 Technical basis	2-1	yielding of SSHS member	3-28
2.1.2 Validity limits	2-1	3.11.7 DESIGN CHECK NO. 7—	
2.1.3 Design capacity factors	2-4	Design capacity of welds to	
2.2 Properties of connection elements	2-5	SSHS member	3-30
2.2.1 General	2-5	3.11.8 DESIGN CHECK NO. 8—	
2.2.2 Component material yield	2-5	Design capacity of bolts in	
stress	2-5	axial tension	3-31
2.2.3 SSHS material properties	2-6	3.11.9 DESIGN CHECK NO. 9—	
2.2.4 Design yield stress for	2-7	Design capacity of welds to	
Australian produced SSHS	2-7	SSHS member	3-33
2.2.5 Design capacity of welds	2-7	3.11.10 DESIGN CHECK NO. 10—	
2.2.6 Design capacity of bolts	2-8	Design capacity of flange	
2.3 References for Sections 1 and 2	2-9	plate in bending	3-35
3 BOLTED END PLATE SPLICE	3-1	3.11.11 DESIGN CHECK NO. 11—	
3.1 Description of connection	3-1	Design capacity due to local	
3.2 Typical detailing of connection	3-3	yielding of SSHS member	3-36
3.3 Detailing considerations	3-4	3.12 Design example	3-37
3.4 Background information	3-6	3.13 Design capacity tables	3-42
3.4.1 Prying action	3-6	3.14 References	3-68
3.4.2 Recent research—Axial	3-7	4 BOLTED MOMENT END PLATE	4-1
tension	3-7	4.1 Description of connection	4-1
3.4.3 Recent research—Combined	3-9	4.2 Typical detailing of connection	4-3
axial tension and bending	3-9	4.3 Detailing considerations	4-4
3.4.4 Relevant international	3-9	4.4 Background information	4-6
codes and specifications	3-9	4.4.1 Research information—	
3.5 Compliance with AS 4100	3-10	Bending	4-6
requirements	3-10	4.4.2 Research information—	
3.6 Basis of design model	3-12	Combined bending and axial	
3.7 Calculation of design actions	3-14	tension/compression	4-8
3.8 Recommended design model—		4.4.3 Relevant international codes	
Connection notation	3-15	and specifications	4-8
3.9 Recommended design model—		4.5 Compliance with AS 4100	
Limits of validity	3-17	requirements	4-9
3.10 Recommended design model—		4.6 Basis of design model	4-10
Summary of design checks	3-18	4.7 Calculation of design actions	4-12
3.11 Recommended design model—		4.8 Recommended design model—	
General	3-19	Connection notation	4-13
3.11.1 DESIGN CHECK NO. 1—		4.9 Recommended design model—	
Detailing requirements	3-19	Limits of validity	4-14
3.11.2 DESIGN CHECK NO. 2—		4.10 Recommended design model—	
Validity limits and minimum		Summary of design checks	4-15
design actions	3-20	4.11 Recommended design model—	
		General	4-17
		4.11.1 DESIGN CHECK NO. 1—	
		Detailing requirements	4-17



	<i>Page</i>		<i>Page</i>
4.11.2 DESIGN CHECK NO. 2— Validity limits and minimum design actions	4-18	4.11.8 DESIGN CHECK NO. 8— Design capacity due to tear out in end plate	4-33
4.11.3 DESIGN CHECK NO. 3— Design capacity of bolts in axial tension	4-19	4.11.9 DESIGN CHECK NO. 9— Design capacity of welds to SSHS member	4-34
4.11.4 DESIGN CHECK NO. 4— Design capacity of welds to SSHS member	4-23	4.12 Design example	4-35
4.11.5 DESIGN CHECK NO. 5— Design capacity of end plate in bending	4-24	4.13 Design capacity tables	4-41
4.11.6 DESIGN CHECK NO. 6— Design capacity of end plate due to punching shear	4-29	4.14 References	4-67
4.11.7 DESIGN CHECK NO. 7— Design capacity of bolts in shear and ply bearing	4-32	5 NOTATION AND ABBREVIATIONS	5-1
		APPENDICES	
		A—Limcon design example output	6-1
		B—ASI Design Guide 24 Comment form	7-1

## LIST OF FIGURES

	<i>Page</i>		<i>Page</i>
Figure 1.1 Connections included in this Design Guide	1-2	Figure 3.13 Plastic hinge mechanism model for 4 sided connection	3-27
Figure 2.1 Definition of element width for RHS flanges	2-3	Figure 3.14 Design example configuration	3-37
Figure 3.1 Typical bolted end plate splice connection configurations	3-1	Figure 4.1 Typical bolted moment end plate connection configurations	4-1
Figure 3.2 Typical connection assemblies utilising bolted end plates	3-2	Figure 4.2 Typical connection assemblies utilising bolted moment end plates	4-2
Figure 3.3 Bolting to circular end plate splice connection	3-3	Figure 4.3 Bolting to two and four sides of rectangular moment end plate connection	4-3
Figure 3.4 Bolting to two and four sides of rectangular end plate splice connection	3-3	Figure 4.4 Clearance required for tensioning bolts	4-5
Figure 3.5 Clearance required for tensioning bolts	3-5	Figure 4.5 Weld induced dishing of the end plates	4-5
Figure 3.6 Weld induced dishing of the flange plates	3-5	Figure 4.6 Bolted moment end plate configurations researched at The University of Sydney	4-7
Figure 3.7 T-stub model for assessment of prying force	3-6	Figure 4.7 Design actions at connection	4-12
Figure 3.8 Generic bolted end plate configurations	3-8	Figure 4.8 Notation for bolted moment end plate design models	4-13
Figure 3.9 Design actions at connection	3-14	Figure 4.9 Punching shear failure modes (from The University of Sydney Eight Bolt Design Model)	4-30
Figure 3.10 Notation for CHS bolted end plate	3-15	Figure 4.10 Minimum edge distances for bolt holes in end plate	4-33
Figure 3.11 Notation for SHS/RHS bolted end plate splice	3-16	Figure 4.11 Design example configuration	4-35
Figure 3.12 Plastic hinge mechanism model for 2 sided connection	3-27		



## LIST OF TABLES

	<i>Page</i>		<i>Page</i>
Table 2.1 Rationalised validity limits for bolted planar connections	2-2	Table 3.13.5 Bolted end plate connection – 2 sided axial tensile capacity ( $\Phi N_{\text{conn}}$ ) $\approx$ 50% of section tensile capacity ( $\Phi N_t$ ) SHS – Grade 450	3-52
Table 2.2 Section slenderness limits to AS 4100 and Eurocode 3	2-3	Table 3.13.6 Bolted end plate connection – 2 sided axial tensile capacity ( $\Phi N_{\text{conn}}$ ) $\approx$ 50% of section tensile capacity ( $\Phi N_t$ ) RHS – Grade 450	3-54
Table 2.3 Section slenderness limits to Eurocode 3 for design grades ( $f_y$ ) 250, 350 and 450 MPa	2-4	Table 3.13.7(a) Bolted end plate connection – 4 sided axial tensile capacity ( $\Phi N_{\text{conn}}$ ) $\approx$ 50% of section tensile capacity ( $\Phi N_t$ ) SHS – Grade 350	3-56
Table 2.4 Minimum plate material properties to AS/NZS 3678	2-5	Table 3.13.7(b) Bolted end plate connection – 4 sided axial tensile capacity ( $\Phi N_{\text{conn}}$ ) $\approx$ 100% of section tensile capacity ( $\Phi N_t$ ) SHS – Grade 350	3-57
Table 2.5 Strength of flat bars to AS/NZS 3679.1 Grade 300	2-6	Table 3.13.8(a) Bolted end plate connection – 4 sided axial tensile capacity ( $\Phi N_{\text{conn}}$ ) $\approx$ 50% of section tensile capacity ( $\Phi N_t$ ) RHS – Grade 350	3-58
Table 2.6 Minimum SSHS material properties to AS/NZS 1163	2-6	Table 3.13.8(b) Bolted end plate connection – 4 sided axial tensile capacity ( $\Phi N_{\text{conn}}$ ) $\approx$ 100% of section tensile capacity ( $\Phi N_t$ ) RHS – Grade 350	3-59
Table 2.7 Design yield stress for SSHS related failure modes for SSHS to AS/NZS 1163	2-7	Table 3.13.9(a) Bolted end plate connection – 4 sided axial tensile capacity ( $\Phi N_{\text{conn}}$ ) $\approx$ 50% of section tensile capacity ( $\Phi N_t$ ) SHS – Grade 450	3-60
Table 2.8 Strength limit state design capacities of equal leg fillet welds per unit length category sp, $\phi = 0.8$ , $k_r = 1.0$ , material thickness $\geq 3$ mm	2-8	Table 3.13.9(b) Bolted end plate connection – 4 sided axial tensile capacity ( $\Phi N_{\text{conn}}$ ) $\approx$ 100% of section tensile capacity ( $\Phi N_t$ ) SHS – Grade 450	3-62
Table 2.9 Strength limit state high strength structural bolts 8.8/S, 8.8/TB, 8.8/TF bolting categories ( $f_{ur} = 830$ MPa)	2-8	Table 3.13.10(a) Bolted end plate connection – 4 sided axial tensile capacity ( $\Phi N_{\text{conn}}$ ) $\approx$ 50% of section tensile capacity ( $\Phi N_t$ ) RHS – Grade 450	3-64
Table 3.1 Rationalised validity limits for bolted end plate splice connection	3-17	Table 3.13.10(b) Bolted end plate connection – 4 sided axial tensile capacity ( $\Phi N_{\text{conn}}$ ) $\approx$ 100% of section tensile capacity ( $\Phi N_t$ ) RHS – Grade 450	3-66
Table 3.13.1(a) Bolted end plate connection axial tensile capacity ( $\Phi N_{\text{conn}}$ ) = 50% of section tensile capacity ( $\Phi N_t$ ) CHS – Grade 250	3-44	Table 4.1 Rationalised validity limits for bolted moment end plate connection	4-14
Table 3.13.1(b) Bolted end plate connection axial tensile capacity ( $\Phi N_{\text{conn}}$ ) = 100% of section tensile capacity ( $\Phi N_t$ ) CHS – Grade 250	3-45	Table 4.2 Bolt material properties	4-22
Table 3.13.2(a) Bolted end plate connection axial tensile capacity ( $\Phi N_{\text{conn}}$ ) = 50% of section tensile capacity ( $\Phi N_t$ ) CHS – Grade 350	3-46	Table 4.3 Head dimensions of bolts Property Class 8.8 to AS/NZS 1252	4-31
Table 3.13.2(b) Bolted end plate connection axial tensile capacity ( $\Phi N_{\text{conn}}$ ) = 100% of section tensile capacity ( $\Phi N_t$ ) CHS – Grade 350	3-48	Table 4.13.1(a) Bolted moment end plate connection – 2 sided moment capacity ( $\Phi M_{\text{conn}}$ ) $\approx$ 50% of section moment capacity ( $\Phi M_s$ ) SHS – Grade 350	4-43
Table 3.13.3 Bolted end plate connection – 2 sided axial tensile capacity ( $\Phi N_{\text{conn}}$ ) $\approx$ 50% of section tensile capacity ( $\Phi N_t$ ) SHS – Grade 350	3-50		
Table 3.13.4 Bolted end plate connection – 2 sided axial tensile capacity ( $\Phi N_{\text{conn}}$ ) $\approx$ 50% of section tensile capacity ( $\Phi N_t$ ) RHS – Grade 350	3-51		



	<i>Page</i>		<i>Page</i>
Table 4.13.1(b) Bolted moment end plate connection – 2 sided moment capacity ( $\Phi M_{conn}$ ) $\approx$ maximum of section moment capacity ( $\Phi M_s$ ) <sub>fl</sub> SHS – Grade 350	4-44	Table 4.13.5(a) Bolted moment end plate connection – 4 sided moment capacity ( $\Phi M_{conn}$ ) $\approx$ 50% of section moment capacity ( $\Phi M_s$ ) SHS – Grade 350	4-55
Table 4.13.2(a) Bolted moment end plate connection – 2 sided moment capacity ( $\Phi M_{conn}$ ) $\approx$ 50% of section moment capacity ( $\Phi M_s$ ) RHS – Grade 350	4-45	Table 4.13.5(b) Bolted moment end plate connection – 4 sided moment capacity ( $\Phi M_{conn}$ ) $\approx$ maximum of section moment capacity ( $\Phi M_s$ ) SHS – Grade 350	4-56
Table 4.13.2(b) Bolted moment end plate connection – 2 sided moment capacity ( $\Phi M_{conn}$ ) $\approx$ maximum of section moment capacity ( $\Phi M_s$ ) <sub>fl</sub> RHS – Grade 350	4-46	Table 4.13.6(a) Bolted moment end plate connection – 4 sided moment capacity ( $\Phi M_{conn}$ ) $\approx$ 50% of section moment capacity ( $\Phi M_s$ ) RHS – Grade 350	4-57
Table 4.13.3(a) Bolted moment end plate connection – 2 sided moment capacity ( $\Phi M_{conn}$ ) $\approx$ 50% of section moment capacity ( $\Phi M_s$ ) SHS – Grade 450	4-47	Table 4.13.6(b) Bolted moment end plate connection – 4 sided moment capacity ( $\Phi M_{conn}$ ) $\approx$ maximum of section moment capacity ( $\Phi M_s$ ) RHS – Grade 350	4-58
Table 4.13.3(b) Bolted moment end plate connection – 2 sided moment capacity ( $\Phi M_{conn}$ ) $\approx$ maximum of section moment capacity ( $\Phi M_s$ ) <sub>fl</sub> SHS – Grade 450	4-49	Table 4.13.7(a) Bolted moment end plate connection – 4 sided moment capacity ( $\Phi M_{conn}$ ) $\approx$ 50% of section moment capacity ( $\Phi M_s$ ) SHS – Grade 450	4-59
Table 4.13.4(a) Bolted moment end plate connection – 2 sided moment capacity ( $\Phi M_{conn}$ ) $\approx$ 50% of section moment capacity ( $\Phi M_s$ ) RHS – Grade 450	4-51	Table 4.13.7(b) Bolted moment end plate connection – 4 sided moment capacity ( $\Phi M_{conn}$ ) $\approx$ maximum of section moment capacity ( $\Phi M_s$ ) SHS – Grade 450	4-61
Table 4.13.4(b) Bolted moment end plate connection – 2 sided moment capacity ( $\Phi M_{conn}$ ) $\approx$ maximum of section moment capacity ( $\Phi M_s$ ) <sub>fl</sub> RHS – Grade 450	4-53	Table 4.13.8(a) Bolted moment end plate connection – 4 sided moment capacity ( $\Phi M_{conn}$ ) $\approx$ 50% of section moment capacity ( $\Phi M_s$ ) RHS – Grade 450	4-63
		Table 4.13.8(b) Bolted moment end plate connection – 4 sided moment capacity ( $\Phi M_{conn}$ ) $\approx$ maximum of section moment capacity ( $\Phi M_s$ ) RHS – Grade 450	4-65



## PREFACE

This new series of connection publications by the Australian Steel Institute (ASI) covering design capacity tables, theory and design of individual structural steel hollow section ('tubular') connections will be known as the Structural Steel Tubular Connections Series: 1<sup>st</sup> edition, 2013 ('Tubular Connection Series'). The Tubular Connection Series details the method of design and provides design capacity tables and detailing parameters for a range of tubular connections commonly used in Australia. Connections have a major engineering and economic importance in steel structures influencing design, detailing, fabrication and erection costs. Standardisation of design approach integrated with industry detailing is the key to minimum costs at each stage. The Tubular Connection Series is written in the same format as and extends the range of the existing 'Structural Steel Connection Series Parts 1 and 2' published by ASI commencing 2007. Each book in the new Tubular Connection Series is numbered as a continuation from the existing series and hence this current book is referred to as 'Tubular Design Guide 24' (TDG24). The Tubular Connection Series replaces and enhances an AISC publication released in 1996 and titled 'Design of structural steel hollow section connections' (often referred to as the 'Blue Book'). With significant international research undertaken in the interim period and new and refined design models available, together with improvements in the performance of Australian produced structural steel hollow sections (SSHS), the time was appropriate to revise and update the Blue Book.

Tubular Design Guide 24 brings together a number of design models for bolted connections between tubular members that lie in the same plane and provide continuity in design actions between the two members associated with the connection. The format and intent of the technical components of TDG24 is to provide sufficient technical basis to allow TDG24 to be a self-standing document, but at the same time, where substantive background technical basis is required, the reader may refer back to both Tubular Design Guide 20 (TDG20) and Handbook 1 of the existing Structural Steel Connection Series.

This has been achieved through extensive local and international literature reviews using ASI's close association with like organisations and searching the wealth of material contained in the ASI Library (the largest steel design library in the Southern Hemisphere). This process consolidated industry best practice, references and research papers. TDG24, in conjunction with TDG20 and Handbook 1, formulates the design models and procedures for the assessment of bolted planar connections between SSHS members.

Following on from the existing Structural Steel Connection Series, the new Tubular Connection Series format, with separate design guides for individual connection types or groupings related to similar functions, is intended to facilitate addition to, or revision of, connection model theory using relevant new local or international research. Connection models developed follow a stylised page format with a numbered DESIGN CHECK procedure to simplify connection capacity assessment. Combined with a worked example and accompanying design capacity tables, each connection model provides a self-standing solution for the design engineer.

Engineering Systems has worked closely with the ASI to further develop their existing Limcon software as the companion program for this new Tubular Connection Series. The latest version of Limcon (V3.6) fully implements the new connection design models and was employed in checking the design tables. The Limcon output for one or more of the worked examples is included in an appendix to each design guide for each connection design type. The program is an efficient tool covering the full range of structural connections, including those beyond the scope of the design capacity tables provided in the Tubular Connection Series.

The existing Structural Steel Connection Series included comment/feedback forms. In the current series, these are replaced by a recently developed web based eForum facility. Every publication, seminar and talk that ASI sponsors has or will have a corresponding thread on the ASI eForum. Users are encouraged to log into the eForum and provide feedback on this current series. The eForum is located off our website at <http://steel.org.au/forum/>

P.W. Key  
A.A. Syam

