

**Tubular Design Guide 26:
Fully welded—Gap planar connections**

by

P.W. Key

and

A.A. Syam

first edition—2014



AUSTRALIAN STEEL INSTITUTE
(ABN)/ACN (94) 000 973 839

**Tubular Design Guide 26:
Fully welded—Gap planar connections**

Copyright © 2014 by AUSTRALIAN STEEL INSTITUTE

Published by: AUSTRALIAN STEEL INSTITUTE

All rights reserved. This book or any part thereof must not be reproduced in any form without the written permission of Australian Steel Institute.

Note to commercial software developers: Copyright of the information contained within this publication is held by Australian Steel Institute (ASI). Written permission must be obtained from ASI for the use of any information contained herein which is subsequently used in any commercially available software package.

FIRST EDITION 2014 (LIMIT STATES)

National Library of Australia Cataloguing-in-Publication entry:

Key, Peter W.

Tubular Design Guide 26: Fully welded—Gap planar connections / Peter W. Key, Arun A. Syam

ISBN 978 1 921476358 (pbk.).

Series: Structural steel tubular connection series.

Includes bibliographical references.

Steel, Structural—Standards – Australia.

Structural engineering.

Syam, Arun A.

Australian Steel Institute.

624.1821021894

Also in this series:

Tubular Design Guide 20: Background and design basis

Tubular Design Guide 21: Bolted bracing connections

Tubular Design Guide 22: Bolted bracing cleats

Tubular Design Guide 23: Plate fitments

Tubular Design Guide 24: Bolted planar connections

Tubular Design Guide 25: Fully welded—Simple planar connections

Tubular Design Guide 27: Fully welded—Overlap planar connections

Disclaimer: The information presented by the Australian Steel Institute in this publication has been prepared for general information only and does not in any way constitute recommendations or professional advice. While every effort has been made and all reasonable care taken to ensure the accuracy of the information contained in this publication, this information should not be used or relied upon for any specific application without investigation and verification as to its accuracy, suitability and applicability by a competent professional person in this regard. The Australian Steel Institute, its officers and employees and the authors and editors of this publication do not give any warranties or make any representations in relation to the information provided herein and to the extent permitted by law (a) will not be held liable or responsible in any way; and (b) expressly disclaim any liability or responsibility for any loss or damage costs or expenses incurred in connection with this publication by any person, whether that person is the purchaser of this publication or not. Without limitation, this includes loss, damage, costs and expenses incurred as a result of the negligence of the authors, editors or publishers.

The information in this publication should not be relied upon as a substitute for independent due diligence, professional or legal advice and in this regards the services of a competent professional person or persons should be sought.



CONTENTS

	<i>Page</i>		<i>Page</i>
LIST OF FIGURES	iv	3.9 Recommended design model—	
LIST OF TABLES	iv	Limits of validity	3-12
PREFACE	v	3.10 Recommended design model—	
ABOUT THE AUTHORS	vi	Summary of design checks	3-14
ACKNOWLEDGEMENTS	vii	3.11 Recommended design model—	
		General	3-15
1 CONCEPT OF DESIGN GUIDES	1-1	3.11.1 DESIGN CHECK NO. 1—	
1.1 Background	1-1	Detailing requirements	3-15
1.2 Included connections	1-2	3.11.2 DESIGN CHECK NO. 2—	
		Validity limits and minimum	
		design actions	3-16
2 TECHNICAL BASIS	2-1	3.11.3 DESIGN CHECK NO. 3—	
2.1 Technical background	2-1	Design capacity due to	
2.1.1 Technical background	2-1	chord face plastification	3-17
2.1.2 Validity limits	2-1	3.11.4 DESIGN CHECK NO. 4—	
2.1.3 Design capacity factors	2-4	Design capacity due to chord	
2.2 Properties of connection elements	2-5	punching shear	3-19
2.2.1 General	2-5	3.11.5 DESIGN CHECK NO. 5—	
2.2.2 Component material yield		Design capacity due to local	
2.2.2 stress	2-5	yielding of brace member	3-21
2.2.3 SSHS material properties	2-6	3.11.6 DESIGN CHECK NO. 6—	
2.2.4 Design yield stress for		Design capacity of welds to	
2.2.4 Australian produced SSHS	2-7	SSHS brace members	3-23
2.2.5 Design capacity of welds	2-7	3.11.7 DESIGN CHECK NO. 7—	
2.2.6 Design capacity of bolts	2-8	Design capacity due to	
2.3 References for Sections 1 and 2	2-9	chord shear	3-25
3 K & N GAP CONNECTIONS	3-1	3.12 Application to KT gap connections	3-27
3.1 Description of connection	3-1	3.12.1 Background information	3-27
3.2 Typical detailing of connection	3-3	3.12.2 Connection classification	3-27
3.3 Detailing considerations	3-4	3.12.3 Design basis	3-29
3.4 Background information	3-5	3.13 Design example	3-30
3.4.1 Recent research	3-5	3.14 Design capacity tables	3-35
3.4.2 Relevant international		3.15 References	3-43
3.4.2 codes and specifications	3-6		
3.5 Compliance with AS 4100			
3.5.1 requirements	3-8	4 NOTATION AND ABBREVIATIONS	4-1
3.6 Basis of design model	3-9	APPENDICES	
3.7 Calculation of design actions	3-10	A—Limcon design example output	5-1
3.8 Recommended design model—		B—ASI Design Guide 26	
3.8.1 Connection notation	3-11	Comment form	6-1



LIST OF FIGURES

	<i>Page</i>		<i>Page</i>		
Figure 1.1	Connections included in this Design Guide	1-2	Figure 3.4	Notation for K & N gapped connections	3-11
Figure 2.1	Definition of element width for RHS flanges	2-3	Figure 3.5	Typical KT Gap connections	3-27
Figure 3.1	Typical K & N and KT gap connection configurations	3-1	Figure 3.6	Classification of KT connections	3-28
Figure 3.2	Typical detailing of K & N gap connections	3-3	Figure 3.7	Design example configuration	3-30
Figure 3.3	Design actions at connection (+ve actions tensile)	3-10			

LIST OF TABLES

	<i>Page</i>		<i>Page</i>		
Table 2.1	Rationalised validity limits for gap planar connections	2-2	Table 3.1	Rationalised validity limits for K & N gap connections	3-12
Table 2.2	Section slenderness limits to AS 4100 and Eurocode 3	2-3	Table 3.2	Maximum d_i/t_i ratios for CHS in compression	3-13
Table 2.3	Section slenderness limits to Eurocode 3 for design grades (f_y) 250, 350 and 450 MPa	2-4	Table 3.13.1	Design capacity of gap K connection CHS – Grade 250	3-36
Table 2.4	Minimum plate material properties to AS/NZS 3678	2-5	Table 3.13.2 (Part 1 of 2)	Design capacity of gap K Connection CHS – Grade 350	3-37
Table 2.5	Strength of flat bars to AS/NZS 3679.1 Grade 300	2-6	Table 3.13.2 (Part 2 of 2)	Design capacity of gap K connection CHS – Grade 350	3-38
Table 2.6	Minimum SSHS material properties to AS/NZS 1163	2-6	Table 3.13.3 (Part 1 of 2)	Design capacity of gap K connection SHS – Grade 350	3-39
Table 2.7	Design yield stress for SSHS related failure modes for SSHS to AS/NZS 1163	2-7	Table 3.13.3 (Part 2 of 2)	Design capacity of gap K connection SHS – Grade 350	3-40
Table 2.8	Strength limit state design capacities of equal leg fillet welds per unit length Category SP, $\phi = 0.8$, $k_r = 1.0$, material thickness ≥ 3 mm	2-8	Table 3.13.4 (Part 1 of 2)	Design capacity of gap K connection SHS – Grade 450	3-41
Table 2.9	Strength limit state high strength structural bolts 8.8/S, 8.8/TB, 8.8/TF bolting categories ($f_{ur} = 830$ MPa)	2-8	Table 3.13.4 (Part 2 of 2)	Design capacity of gap K connection SHS – Grade 450	3-42



PREFACE

This new series of connection publications by the Australian Steel Institute (ASI) covering design capacity tables, theory and design of individual structural steel hollow section ('tubular') member connections will be known as the Structural Steel Tubular Connections Series: 1st edition 2013 ('Tubular Connection Series'). The Tubular Connection Series details the method of design and provides design capacity tables and detailing parameters for a range of tubular connections commonly used in Australia. Connections have a major engineering and economic importance in steel structures influencing design, detailing, fabrication and erection costs. Standardisation of design approach integrated with industry detailing is the key to minimum costs at each stage. The Tubular Connection Series is written in the same format as and extends the range of the existing 'Structural Steel Connection Series Parts 1 and 2' published by ASI commencing 2007. Each book in the new Tubular Connection Series is numbered as a continuation from the existing series and hence this current book is referred to as 'Tubular Design Guide 26' (TDG26). The Tubular Connection Series replaces and enhances an AISC publication released in 1996 and titled 'Design of structural steel hollow section connections' (often referred to as the 'Blue Book'). With significant international research undertaken in the interim period and new and refined design models available, together with improvements in the performance of Australian produced structural steel hollow sections (SSHS), the time was appropriate to revise and update the Blue Book.

Tubular Design Guide 26 on fully welded gap planar connections covers connections of two or more brace members framing into the same side of a chord member, where a gap exists between the adjacent brace members along the connected face of the chord member. The format and intent of the technical components of TDG26 is to provide sufficient technical basis to allow TDG26 to be a self-standing document, but at the same time, where substantive background technical basis is required, the reader may refer back to both Tubular Design Guide 20 (TDG20) and Handbook 1 of the existing Structural Steel Connection Series.

This has been achieved through extensive local and international literature reviews using ASI's close association with like organisations and searching the wealth of material contained in the ASI Library (the largest steel design library in the Southern Hemisphere). This process consolidated industry best practice, references and research papers. TDG26, in conjunction with TDG20 and Handbook 1, formulates the design models and procedures for the assessment of fully welded connections between multiple SSHS brace members and an SSHS chord member where a gap exists.

Following on from the existing Structural Steel Connection Series, the new Tubular Connection Series format, with separate design guides for individual connection types or groupings related to similar functions, is intended to facilitate addition to, or revision of, connection model theory using relevant new local or international research. Connection models developed follow a stylised page format with a numbered DESIGN CHECK procedure to simplify connection design capacity assessment. Combined with a worked example and accompanying design capacity tables, each connection model provides a self-standing solution for the design engineer.

Engineering Systems has worked closely with the ASI to further develop their existing Limcon software as the companion program for this new Tubular Connection Series. The latest version of Limcon (V3.6) fully implements the new connection design models and was employed in checking the design tables. The Limcon output for one or more of the worked examples is included in an appendix to each design guide for each connection design type. The program is an efficient tool covering the full range of structural connections, including those beyond the scope of the design capacity tables provided in the Tubular Connection Series.

The existing Structural Steel Connection Series included comment/feedback forms. In the current series, these are replaced by a recently developed web based eForum facility. Every publication, seminar and talk that ASI sponsors has or will have a corresponding thread on the ASI eForum. Users are encouraged to log into the eForum and provide feedback on this current series. The eForum is located off our website at <http://steel.org.au/forum/>

P.W. Key
A.A. Syam

