## **CONTENTS**

	Page	Pa	ge
List of figures	V	10.7 DESIGN CHECK NO. 7—Design	
List of tables	vi	capacity of supported member	
Preface	vii		19
About the author	viii	10.8 DESIGN CHECK NO. 8—Beam	
About the contributing author and editor	viii		20
Acknowledgements	ix	10.9 DESIGN CHECK NO. 9—Local	
, tolkilo mougomente		stability of coped supported	
1 CONCEPT OF DESIGN GUIDE	1		21
1.1 Background	1	10.10 DESIGN CHECK NO. 10—Local	- :
ŭ			22
2 DESCRIPTION OF CONNECTION	2	, , , ,	22
		•	23
3 TYPICAL DETAILING OF CONNECTI		10.10.2 Double-slace confliction	20
3.1 Double angle cleat	3	11 RECOMMENDED DESIGN MODEL—	
3.2 Single angle cleat	4	SINGLE ANGLE CLEAT—	
	_		.24
4 DETAILING CONSIDERATIONS	5	11.1 DESIGN CHECK NO. 1—	
E COMPLIANCE VALLET A C. 4400			25
5 COMPLIANCE WITH AS 4100		11.2 DESIGN CHECK NO. 2—	
REQUIREMENTS FOR CONNECTION	NS 7	Design capacity of bolts to	
6 BACKGROUND INFORMATION	0		26
6 BACKGROUND INFORMATION	0	11.3 DESIGN CHECK NO. 3—	20
7 BASIS OF DESIGN MODEL—DOUBL	F	Design capacity of bolts to	
ANGLE CLEATS			27
ANGLE OLLATO		11.3.1 Alternative 'A'—Single line	21
8 BASIS OF DESIGN MODEL—SINGLE			27
ANGLE CLEAT		11.3.2 Alternative 'B'—Double line	21
			27
9 CONNECTION GEOMETRY	11	11.4 DESIGN CHECK NO. 4—Design	21
		capacity of angle cleat (Shear,	
10 RECOMMENDED DESIGN MODEL—			28
DOUBLE ANGLE CLEATS—		11.5 DESIGN CHECK NO. 5—Design	20
SUMMARY OF CHECKS	12	capacity of supported member	
10.1 DESIGN CHECK NO. 1—			29
Detailing limitations	13	11.6 DESIGN CHECK NO. 6—Design	23
10.2 DESIGN CHECK NO. 2—		capacity of supported member	
Design capacity of bolts			30
to supporting member	14	11.7 DESIGN CHECK NO. 7—Design	50
10.3 DESIGN CHECK NO. 3—		capacity of supported member	
Design capacity of bolts			31
to supported member	15	11.8 DESIGN CHECK NO. 8—Beam	01
10.3.1 Alternative 'A'—Single line of			32
bolts to supported member	15	11.9 DESIGN CHECK NO. 9—Local	32
10.3.2 For Alternative 'B'—Double lin	ne	stability of coped supported	
of bolts to supported member			33
10.4 DESIGN CHECK NO. 4—Design	n	11.10 DESIGN CHECK NO. 10—Local	55
capacity of angle cleats (Shear,			34
bending, block shear)	16		34
10.5 DESIGN CHECK NO. 5—Design	n	•	35
capacity of supported member		11.10.2 Double-sided collinection	JJ
(Shear—Uncoped or coped)	17	12 OTHER DESIGN CONSIDERATIONS	36
10.6 DESIGN CHECK NO. 6—Design	n		
capacity of supported member		13 REFERENCES	.37
(Block shear—Coped section)	18		
		Pa	ge





iii

14 DESIGN EXAMPLES	38		Page
14.1 Design example No. 1—			
Connection capacity with single-sided double AC connection to supporting column	38	15.2 Configuration B—Double angle double line of bolts to supported member	
14.2 Design example No. 2— Connection capacity with single-sided single AC		15.3 Configuration C—Single angle cleat single line of bolts to	•
connection to supporting beam	41	supported member 15.4 Configuration D—Single angle	54
15 DESIGN CAPACITY TABLES 15.1 Configuration A—Double angle	44	cleat double line of bolts to supported member	57
cleat single line of bolts to		APPENDICES	
supported member	44	A Limcon software	58
		B ASI Design Guide 5	
		comment form	65



